




**MADE IN KOREA**

Eco-Friendly &  
 Fully Closed Dry Cleaning  
 Machine



**MADE IN ITALY**

Ultimate Generation  
 Multilingual Computer with  
 Automatic & Manual Control  
 Wide Display to follow each  
 program step by step.

- ✓ Two or three automatic self cleaning tanks of high capacity.
- ✓ Nylon self cleaning filter or cartridge with active carbons.
- ✓ Basket, distillator, air channel, button trap, filters housing, water separator in stainless steel.
- ✓ Danfoss valves for saving water, Still float switch level control (Overfill Prevented)
- ✓ Water level control in still over the heating elementally stainless steel.
- ✓ Thermal overload relays on all motors.
- ✓ Closed circuit with Copeland scroll refrigerator (the most silent & efficient on the market).
- ✓ Double lint filter with huge surface and possible automatic self cleaning.
- ✓ Distillator condenser in Fibreglass.

Model	Capacity Dry Wt Per Charge	Basket		Tank	Capacity (Lt.) Distillator / Nylon Filter	Drive Motor		Pump / Fan Refrigerator Air Compressor	Heating El Distillator / Air Heater	Steam Power Electric Power	Steam Compressed Air Water	Consumption With / Without Distillation Water (lt./cycle) Steam(kg/hr.) Electricity (kwh)	Connection Air / water Inlet / Water Outlet / Steam Inlet / Condensate Outlet	Dimension Width Depth Height	Net Weight / Shipping Wt. Shipping Size (wxdxh) Shipping Volume
		Dia X Depth	Volume/door Dia.			Washing	Extracting								
PM-200	10 / 12	700 x 520	135	160 / 35	2.2 KW	0.55 KW / 1.1 KW	2.0 KW	7.5 KW	6 KW	4.5	140(45)	1/4"	1600	950 / 2090	
		200 / 420			2.2 KW	0.35 KW	4.2 KW	18 KW	6	40(15)	1/2" / 1/2"	1400			
PM-300	15 / 17	850 x 530	115	160 / 35	2.2 KW	0.55 KW / 1.1 KW	2.0 KW	4.5 KW	6 KW	4.5	140(45)	1/4"	1600	980 / 2156	
		300 / 420			2.2 KW	0.35 KW	4.2 KW	18 KW	6	50(22)	1/2" / 1/2"	1420			
PM-360	18 / 20	900 x 565	115	160 35	2.2 KW	0.55 KW / 2.1 KW	2.0 KW	7.5 KW	7 KW	4.5	150(50)	1/4"	1600	1040 / 2288	
		360 / 420			2.2 KW	0.35 KW	4.8 KW	19.5 KW	6	50(22)	1/2" / 1/2"	1420			
PM-400	20 / 22	1000 x 520	140	215 / 50	2.2 KW	0.55 KW / 2.2 KW	2.0 KW	12.0 KW	7 KW	5	180(60)	1/4"	2080	1550 / 2680	
		408 / 420			2.2 KW	0.35 KW	4.8 KW	24 KW	8	70(40)	1/2" / 1/2"	1450			
PM-500	25 / 28	1060 x 570	180	300 / 66	3.5 KW	0.55 KW / 2.2 KW	3.0 KW	16 KW	9.5 KW	5	190(100)	1/4"	2250	2000 / 4450	
		503 / 520			3.5 KW	0.35 KW	4.8 KW	31 KW	8	90(50)	1/2" / 1/2"	1680			
PM-700	33 / 35	1060 x 750	180	330 / 66	4.0 KW	1.0 KW / 1.5 KW	1.5 KW	16 KW	14 KW	5	190(100)	1/4"	2250	2800 / 6150	
		670 / 520			4.0 KW	0.35 KW	7.5 KW	35 KW	8	90(50)	1/2" / 1/2"	1700			
															2240

**Note:** a) All Dimensions are in MM. Standard Machines Operate on 415 ±10%, 3 Phase, 50HZ, CYS AC Electric Supply, Special Voltage on request.  
 b) Machines are also made to order as per customer's requirement & specifications.