

## Washer Extractor & Dryer Combo | Fully Automatic

### Features:

- ✓ Fully Automatic Rigid Mounted Industrial Washer Extractor & Dryer COMBO in which inner and outer cylinder interface adopt a face to face mode can effectively prevent accidental damage to cloth and leather
- ✓ It adopts SS304 stainless steel panels and inner pot for longer service life, and also much easier to be cleaned
- ✓ Liquid cylinder is with a special anti-corrosion treatment, very durable
- ✓ The whole washing tank system is installed hard mounted on the base frame heavy plate and damping devices, heavy duty bearing housing drive through pulley with belt driven type
- ✓ It is with automatic detergent separation container, neither washing powder accumulates nor the washing additives cannot fully dissolve and then rot the cloth and leather
- ✓ It is fully controlled by the computer, with VFD Drive to adjust the speed, with man-machine conversation to adjust washing program, with clear LCD 7" Touch screen display. With failure and functional self-checking system to make it easier to maintain
- ✓ Electrical control components all adopt high-quality components, motor adopts high-quality special motor



COMBO - 40			
Rated Capacity	40 KG	Weight	1150 KG
Model Number	NXCE-40	Voltage	3 Phase – 415
Loading Type	Front Loading	Drum Size	Dia 1000 x 850 mm
Usage / Application	24 Hours	Processing Time	1 Hour 15 Minutes
Motor Power	7.5 HP	Air Pressure Bar	N/A
Size / Dimension	1450 x 1920 x 2040 mm	Phase	3 Phase / 50 Hz
Cycle Timing	1 Hour 15 Minutes	Rotation Speed (RPM)	650 (G-Force 250)
Design	Front Load / Electric Heated	Rotor Speed (RPM)	N/A
Water Heater Load	18 KW	Working Capacity (KG/Hr.)	KG
Dryer Heater Load	15 KW	Display	YES (PLC SYSTEMS)
Water Inlet Valve	1½"	Door Size	640 x 640 mm
Water Drain Valve	3"	Express Wash	YES
Washing Type	Forward & Reverse	Fabric	All Type Fabric
Water Consumption	1:9 / 1:10	Automation Grade	Automatic